

GHS COMPLIANT SAFETY DATA SHEET

TO COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR.1910.1200
& THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS

SECTION 1: IDENTIFICATION

| | |
|-------------------------|---|
| PRODUCT NAME | Resiflow® L-68 |
| MFR.'S CODE ID/SYNONYMS | Resiflow® L-68 |
| CAS NUMBER | Mixture (see Sections 3 or 8) |
| PRODUCT USE | Flow control agent for liquid coatings |
| RESTRICTIONS ON USE | For industrial use only |
| MANUFACTURER/SUPPLIER | Estron Chemical, Inc. |
| ADDRESS | 807 North Main Street, Calvert City, KY 42029 USA |
| GENERAL INFORMATION | (270) 395-4195 |
| EMERGENCY TELEPHONE | CHEMTREC (800) 424-9300 |





SECTION 2: HAZARDS IDENTIFICATION

Signal Word: *Danger*

GHS Classification

| Physical | Health | Environmental |
|--------------------------------|--|--|
| Flammable Liquids – Category 3 | Acute Toxicity (Dermal, Inhalation) – Category 4 Skin Corrosion/Irritation – Category 2 Eye Damage/Irritation – Category 2A Carcinogenicity – Category 2 Toxic to Reproduction – Category 2 Specific Target Organ Toxicity, Single Exposure (Respiratory System) – Category 3 Specific Target Organ Toxicity, Repeated Exposure (Liver, Kidney, Central Nervous System) – Category 2 Aspiration Hazard – Category 1 | Hazardous to the Aquatic Environment, Acute Hazard – Category 2 Hazardous to the Aquatic Environment, Chronic Hazard – Category 2 |

GHS Label

| | | | |
|--|--|--|--|
|  Symbols: Flame |  Health Hazard |  Exclamation Mark |  Environment |
| Hazard Statements H226: Flammable liquid and vapour H304: May be fatal if swallowed and enters airways H312: Harmful in contact with skin H315: Causes skin irritation H319: Causes serious eye irritation H332: Harmful if inhaled H335: May cause respiratory irritation H351: Suspected of causing cancer H361: Suspected of damaging fertility or the unborn child. H373: May cause damage to organs (Liver, Kidney, Central Nervous System) through prolonged or | | Precautionary Statements <i>Prevention</i> P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking. P233: Keep container tightly closed. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/light/equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P260: Do not breathe dust/fume/gas/mist/vapours/spray. P264: Wash exposed skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. | |

| | |
|--|--|
| <p>repeated exposure H411: Toxic to aquatic life with long lasting effects</p> | <p>P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.</p> <p><i>Response</i> P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302+352: IF ON SKIN: Wash with soap and water. P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P308+313: IF exposed or concerned: Get medical advice/attention. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P321: Specific treatment (see supplemental first aid instructions on this label) P331: Do NOT induce vomiting. P332+313: If skin irritation occurs: Get medical advice/attention. P337+313: If eye irritation persists get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P370+378: In case of fire: Use foam, dry chemical powder or carbon dioxide to extinguish. P391: Collect spillage.</p> <p><i>Storage</i> P403+233+235: Store in a well ventilated place. Keep container tightly closed. Keep cool. P405: Store locked up.</p> <p><i>Disposal</i> P501: Dispose of contents/container to an authorized hazardous waste handler.</p> |
|--|--|

HAZARDS NOT OTHERWISE CLASSIFIED: None identified.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENTS | CAS # | % | CLASSIFICATION | H CODES |
|-----------------------|-----------|-------------|--|--|
| Xylene | 1330-20-7 | 40.0 - 41.0 | Flammable Liquids – Category 3 Acute Toxicity (Dermal, Inhalation) – Category 4 Skin Corrosion/Irritation – Category 2 Eye Damage/Irritation – Category 2A Carcinogenicity – Category 2 Toxic to Reproduction – Category 2 Specific Target Organ Toxicity, Single Exposure (Respiratory System) – Category 3 Specific Target Organ Toxicity, Repeated Exposure (Liver, Kidney, Central Nervous System) – Category 2 Aspiration Hazard – Category 1 Hazardous to the Aquatic Environment, Acute Hazard – Category 2 Hazardous to the Aquatic Environment, Chronic Hazard – Category 2 | H226 H312, H332 H315 H319 H351 H361 H335 H373 H304 H401 H411 |

Component Breakdown of Xylene:

| | | | |
|---------------|-----------|-------------|---|
| Mixed Xylenes | 1330-20-7 | 30.0 - 41.0 | Flammable Liquids – Category 3 Acute Toxicity (Dermal, Inhalation) – Category 4 Skin Irritation – Category 2 Eye Irritation – Category 2A Specific Target Organ Toxicity, Single Exposure (Respiratory System) – Category 3 Specific Target Organ Toxicity, Repeated Exposure (Liver, Kidney, Central Nervous System) – Category 2 Aspiration Hazard – Category 1 Hazardous to the Aquatic Environment, Acute Hazard – Category 2 Hazardous to the Aquatic Environment, Chronic Hazard – Category 2 |
|---------------|-----------|-------------|---|

| | | | |
|---------------------|-----------------|-------------------|---|
| <i>Ethylbenzene</i> | <i>100-41-4</i> | <i>0.0 - 12.3</i> | <i>Flammable Liquids – Category 3 Acute Toxicity (Inhalation) – Category 4 Specific Target Organ Toxicity, Single Exposure (Respiratory Tract Irritation, Narcotic Effects) – Category 3 Eye Irritation – Category 2B Skin Corrosion/Irritation – Category 2 Carcinogenicity (Inhalation) – Category 2 Hazardous to the Aquatic Environment, Acute Hazard – Category 2</i> |
| <i>Toluene</i> | <i>108-88-3</i> | <i>0.0 – 2.1</i> | <i>Flammable Liquids – Category 3 Acute Toxicity (Inhalation) – Category 4 Specific Target Organ Toxicity, Single Exposure (Respiratory Tract Irritation, Narcotic Effects) – Category 3 Skin Corrosion/Irritation – Category 2</i> |
| <i>Cumene</i> | <i>98-82-8</i> | <i>0.0 - 0.4</i> | <i>Flammable Liquids – Category 3 Carcinogenicity – Category 2 Acute Toxicity (Inhalation) – Category 3 Acute Toxicity (Oral) – Category 4 Specific Target Organ Toxicity, Single Exposure (Respiratory System) – Category 3 Aspiration Hazard – Category 1 Hazardous to the Aquatic Environment, Acute Hazard – Category 2 Hazardous to the Aquatic Environment, Chronic Hazard – Category 2</i> |

(See Section 8 for Exposure Limits)

| NON-HAZARDOUS INGREDIENTS | CAS # | % |
|----------------------------------|--------------|-------------|
| Acrylic Polymer | Proprietary | 59.0 - 60.0 |

SECTION 4: FIRST-AID MEASURES

SYMPTOMS OF EXPOSURE

ACUTE Eye, skin or respiratory tract irritation. Coughing or sneezing. Drowsiness or dizziness.

DELAYED Stinging, tearing, redness and swelling of the eyes. Drying, cracking, redness or burning of the skin. Respiratory tract irritation, difficulty breathing.

INHALATION Harmful if inhaled. May cause respiratory irritation. Do not inhale vapours, mists or dusts. Symptoms include possible discomfort; cough, sneezing, drowsiness or dizziness. If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing.

SKIN CONTACT Harmful in contact with skin. Causes skin irritation. Take off contaminated clothing. Rinse skin with water/shower. Prolonged or repeated contact may dry the skin. If skin irritation occurs: Get medical advice/attention.

EYE CONTACT Causes serious eye irritation. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention.

INGESTION Do NOT induce vomiting. If ingested, immediately call a POISON CENTER or doctor/physician.

SPECIFIC TREATMENT No other specific treatments are known or have been identified.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABILITY CLASSIFICATION Flammable Liquid Class IC

FLAMMABLE LIMITS
LEL: 1.0 %, by volume of solvent.
UEL: 7.0 %, by volume of solvent.

HAZARDOUS COMBUSTION PRODUCTS Carbon Dioxide, Carbon Monoxide.

EXTINGUISHING MEDIA Dry Chemical, Foam, CO₂.

UNUSUAL FIRE AND EXPLOSION HAZARDS Solvent vapors may travel in the work place. Since even residual amounts can ignite explosively, ensure all ignition sources are removed from the area. Solid streams of water may spread fire.

SPECIAL FIRE FIGHTING PROCEDURES Wear self-contained breathing apparatus and protective suit when fighting fire. Solid streams of water may spread the fire. Do not allow run-off to enter public drainage systems or open water courses.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full (Bunker) protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

| | |
|---------------------------------------|--|
| PERSONAL PRECAUTIONS | Prevent contact with skin, eyes and clothing. Ensure adequate ventilation. |
| PROTECTIVE EQUIPMENT | See Personal Protective Equipment in Section 8. |
| EMERGENCY PROCEDURES | Avoid unnecessary exposure to bystanders, prevent contact with open flames or high heat sources. Isolate the area and eliminate all ignition sources. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. |
| ENVIRONMENTAL PRECAUTIONS | Obey relevant local, state, provincial and federal laws and regulations. Do not allow the product to enter public drainage systems or open water courses. |
| METHODS AND MATERIALS FOR CLEANING UP | Absorb the product onto vermiculite, floor absorbent or other absorbent materials, such as dry-lime, sand, or soda ash. Sweep or scoop into a suitable container for disposal. Ventilate area and wash spill site after material pickup is complete. |

SECTION 7: HANDLING AND STORAGE

| | |
|-------------------------------|--|
| PRECAUTIONS FOR SAFE HANDLING | Prevent contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not breathe vapors. Use with adequate ventilation. Ground and bond all containers and handling equipment. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges. Emptied containers may still be hazardous. Do not cut, drill, grind, weld or perform similar actions on or near empty containers. |
| CONDITIONS FOR SAFE STORAGE | Store in cool, dry, well-ventilated areas. Keep containers tightly closed. Do not store near extreme heat, open flame or sources of ignition. Store locked up. |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| INGREDIENTS | CAS # | % | ACGIH TLV | OSHA PEL |
|---------------------|-----------------|-------------------|-------------------------|-------------------------|
| Acrylic Polymer | Proprietary | 59.0 - 60.0 | <i>None established</i> | <i>None established</i> |
| Xylene | 1330-20-7 | 40.0 - 41.0 | 100 ppm | 100 ppm |
| <i>Ethylbenzene</i> | <i>100-41-4</i> | <i>0.0 - 12.3</i> | 100 ppm | 100 ppm |
| <i>Toluene</i> | <i>108-88-3</i> | <i>0.0 - 2.1</i> | 50 ppm (Skin) | 150 ppm |
| <i>Cumene</i> | <i>98-82-8</i> | <i>0.0 - 0.4</i> | 50 ppm | 50 ppm |

APPROPRIATE ENGINEERING CONTROLS Showers, eyewash stations and explosion-proof ventilation systems.

PERSONAL PROTECTIVE EQUIPMENT

| | |
|------------------|---|
| EYE/FACE | Chemical splash goggles or face shield. |
| SKIN | Wear resistant gloves (consult you safety equipment supplier) and impervious protective clothing as appropriate to prevent skin contact. |
| RESPIRATORY | An appropriate NIOSH approved respirator where exposure limits are exceeded. |
| HYGIENE MEASURES | Handle in accordance with good industrial hygiene and safety practices. When using, do not eat, drink or smoke. Wash face and hands before breaks and at the end of work. Wash contaminated clothing before re-use. |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------|--|--|-----------------------------|
| APPEARANCE | Clear to slightly hazy liquid | ODOR | Strong, aromatic |
| ODOR THRESHOLD | No test data available | pH | No test data available |
| MELTING POINT | No test data available | BOILING POINT/RANGE | 139 °C @ 760 mmHg |
| FLASH POINT | 26 - 27 °C, (79 - 81 °F) | EVAPORATION RATE | 0.76 (BuAc = 1) |
| FLAMMABILITY | Flammable Liquid Class IC | | |
| FLAMMABLE LIMITS | LOWER 1.0 %, <i>by volume of solvent</i> | UPPER 7.0 %, <i>by volume of solvent</i> | |
| VAPOR PRESSURE | 7 - 9 mmHg @ 20 °C | VAPOR DENSITY | 3.7 (Air = 1) |
| RELATIVE DENSITY | No test data available | SOLUBILITY IN H ₂ O | <i>Solvent - Negligible</i> |

| | | | |
|--|--|-----------------------------|---------------------------------------|
| PARTITION COEFFICIENT (n-octanol/water) | <i>Solvent</i> – Log P _{ow} = 3.16 <i>Polymers</i> – No data available | AUTOIGNITION TEMPERATURE | <i>Polymers</i> - Nil 432 - 530 °C |
| DECOMPOSITION TEMPERATURE | No test data available | VISCOSITY | No test data available |
| % VOLATILE | 40 - 41% | SOFTENING POINT | No test data available |

SECTION 10: STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| REACTIVITY | This product does not pose a significant reactivity hazard when stored appropriately (see Section 7). |
| STABILITY | This product is stable when stored appropriately (see Section 7). |
| CONDITIONS TO AVOID | All ignition sources, heat and open flames. |
| INCOMPATIBLE PRODUCTS | Strong oxidizers, acids, alkalis and amines. |
| HAZARDOUS DECOMPOSITION PRODUCTS | Carbon Dioxide, Carbon Monoxide. |
| POSSIBILITY OF HAZARDOUS REACTIONS | Will not occur |

SECTION 11: TOXICOLOGICAL INFORMATION

SYMPTOMS OF EXPOSURE

| | |
|---------|--|
| ACUTE | Eye, skin or respiratory tract irritation. Coughing or sneezing. Drowsiness or dizziness. |
| DELAYED | Stinging, tearing, redness and swelling of the eyes. Drying, cracking, redness or burning of the skin. Respiratory tract irritation, difficulty breathing. |

ACUTE TOXICITY

| | | | |
|---------------------|---|---|---|
| INHALATION | Harmful if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause drowsiness or dizziness. | | |
| SKIN | Harmful in contact with skin. Causes skin irritation. | | |
| EYES | Causes serious eye irritation. | | |
| INGESTION | Harmful if swallowed – may enter lungs if swallowed or vomited. | | |
| INHALATION TOXICITY | LC ₅₀ Rat, 4 h | Xylene Toluene Polymers | 6700 ppm, causes irritation. 8000 mg/L Not established |
| DERMAL TOXICITY | LD ₅₀ Rabbit | Xylene Ethylbenzene Polymers | 1,100 mg/kg > 5,000 mg/kg Not established |
| SKIN IRRITATION | Draize, Rabbit, 24 hours | Xylene | 500 mg Moderate, causes skin irritation |
| EYE IRRITATION | Draize, Rabbit, 24 hours | Xylene Ethylbenzene | 87 mg Severe, causes eye irritation 500 mg Moderate, causes eye irritation |
| ORAL TOXICITY | LD ₅₀ Rat | Xylene Ethylbenzene Toluene Polymers | 3,523 mg/kg 5,460 mg/kg 2,600 mg/kg Not established |
| SENSITIZATION | Draize, Rabbit | | Not established |

CHRONIC EFFECTS

| | |
|-----------------|--|
| CARCINOGENICITY | Solvent components are suspected of causing cancer. Ethylbenzene IARC Classified 2B (Possible for Humans), ACGIH A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans) |
|-----------------|--|

| | |
|-----------------------|---|
| MUTAGENIC EFFECTS | Ethylbenzene – Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast. |
| REPRODUCTIVE TOXICITY | Animal testing did not show any effects on fertility. Studies with laboratory animals indicate the solvent(s) used in this product can cause damage to the fetus. |
| TARGET ORGAN EFFECTS | Respiratory Tract Irritation, Liver, Kidney, Central Nervous System. |

SECTION 12: ECOLOGICAL INFORMATION

| | | | |
|-------------------------------|--|--------------|----------------------------------|
| ECOTOXICITY | Toxic to aquatic life with long lasting effects. | | |
| TOXICITY TO FISH | LC ₅₀ Oncorhynchus mykiss, 96 h | Xylene | 2.6 mg/l |
| | | Ethylbenzene | 4.2 mg/l |
| | | Polymers | Not established |
| TOXICITY TO DAPHNIA | EC ₅₀ Daphnia magna | Xylene | 1 mg/l, 24 h |
| | | Ethylbenzene | 1.8 mg/l, 48 h |
| | | Polymers | Not established |
| TOXICITY TO ALGAE | EC ₅₀ Psuedokirchneriella Subcapitata, 72 h | Xylene | 4.36 mg/l |
| | | Ethylbenzene | 5.4 mg/l |
| | | Polymers | Not established |
| PERSISTANCE AND DEGRADABILITY | Inoculum, activated sludge | Xylene | 72%, 20 d, Readily biodegradable |
| | | Ethylbenzene | 70%, 28 d, Readily biodegradable |
| BIOACCUMULATIVE POTENTIAL | Partition coefficient (log K _{ow}) | Xylene | 2.92 |
| | | Ethylbenzene | 3.15 |
| MOBILITY IN SOIL | The solvent in this product is a mobile liquid. | | |
| OTHER ADVERSE EFFECTS | None known | | |

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Dispose of in accordance with local, state and federal regulations. Destroy by incineration with off-gas scrubber. Do not discharge effluent containing this product into lakes, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of the National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact you State Water Board or Regional Office of the Environmental Protection Agency.

US EPA WASTE NUMBER & DESCRIPTION No information available

SECTION 14: TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

U.S. DOT

For ground transportation ONLY:

Proper Shipping Name: Resin solution, *flammable (mixed xylenes)*.

Classification: 3

UN#: 1866

Packing Group: III

Hazard Label: Flammable liquid

Note: Not a Marine Pollutant, by D.O.T. standards

ICAO / IATA

Proper Shipping Name: Resin solution, *flammable (mixed xylenes)*.

Classification: 3

UN#: 1866

Packing Group: III

Hazard Label: Flammable liquid

All other transport:

Proper Shipping Name: Resin solution, *flammable (mixed xylenes)*.

Classification: 3

UN#: 1866

Packing Group: III

Hazard Label: Flammable liquid, Marine Pollutant

IMDG

Proper Shipping Name: Resin solution, *flammable (mixed xylenes)*.

Classification: 3

UN#: 1866

Packing Group: III

EmS#: F-E, S-E

Environmental Hazard: Marine Pollutant

Hazard Label: Flammable liquid, Marine Pollutant

ADR/RID

Proper Shipping Name: Resin solution, *flammable (mixed xylenes)*.

Classification: 3

UN#: 1866

Packing Group: III

Environmental Hazard: Marine Pollutant

Hazard Label: Flammable liquid, Marine Pollutant

SECTION 15: REGULATORY INFORMATION

The components in this product are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories as indicated by an "X":

| | | |
|--------|--|---|
| AICS | Australian Inventory of Chemical Substances | X |
| DSL | Canadian Domestic Substances List | |
| ECL | Korean Existing Chemicals List | |
| ECN | Taiwan Chemical Substances List | |
| ELINCS | European List of Notified Chemical Substances | |
| ENCS | Japanese Existing and New Chemical Substances | |
| IECSC | Inventory of Existing Chemical Substances in China | |
| ISRAEL | Proposed Israel Hazardous Substances List | |
| NDSL | Canadian Non-Domestic Substances List | |
| NZIoC | New Zealand Inventory of Chemicals | X |
| PICCS | Philippines Inventory of Chemicals and Chemical Substances | |
| SWISS | Giftelist I and Inventory of Notified New Substances | |
| TSCA | US Toxic Substances Control Act | X |

INTERNATIONAL REGULATIONS

EU REGULATION (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization, *Substances of Very High Concern*: This product does not contain any SVHC listed substances.

EINECS All of the components of this product are included on the European Inventory of Existing Commercial Chemical Substances.

C.D. 96/82/EC Council Directive 96/82/EC, Annex I not mentioned by name. With regard to possibly appropriate decomposition products see Chapter 10.

CANADA WHMIS Class B-2: Flammable Liquid
Class D-2A: Very Toxic Material Causing Other Toxic Effects
Class D-2B: Toxic Material Causing Other Toxic Effects

FEDERAL REGULATIONS

SARA 313 This product may contain chemicals (xylene, ethylbenzene, toluene) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA Section 311/312 (40 CFR 370) Hazard Categories

| | |
|-----------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |

Pressure Hazard No
Reactivity Hazard No

CERCLA This product, as supplied, contains substances (xylene, ethylbenzene, toluene) regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional or state level pertaining to releases of this product.

CLEAN WATER ACT This product contains substances (xylene, ethylbenzene, toluene) regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CLEAN AIR ACT This product contains substances (xylene, ethylbenzene, toluene, cumene) regulated as hazardous air pollutants (HAPS under Section 112 of the Clean Air Act Amendments of 1990).

OTHER FEDERAL None known

U.S. STATE REGULATIONS

RIGHT TO KNOW The Listing requirements of the Right to Know (RTK) legislation varies by state. All information for NJ, PA, MA and other states can be derived from the listing of hazardous and non-hazardous components in Sections 2 and 15 of this Safety Data Sheet.

CALIFORNIA PROP 65 **CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):**
WARNING! This product contains a chemical(s) known to the State of California to cause cancer.

| Component | CAS # | Amount |
|------------------|--------------|---------------|
| Xylene | 1330-20-7 | 24.0 - 41.0 % |
| Ethylbenzene | 100-41-4 | 0.0 - 14.3 % |
| Toluene | 108-88-3 | 0.0 - 0.2 % |
| Cumene | 98-82-8 | 0.0 - 0.4 % |
| Benzene | 71-43-2 | Trace |

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):
WARNING! This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

| Component | CAS # | Amount |
|------------------|--------------|---------------|
| Toluene | 108-88-3 | 0.0 - 0.2 % |
| Benzene | 71-43-2 | Trace |

SECTION 16: OTHER INFORMATION

DISCLAIMER This product is intended for industrial use only and should be used in accordance with the manufacturer's recommendations. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. This SDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

DATE OF REVISION April 18, 2016, *replaces the June 9, 2015 version.*

REASON FOR REVISION Revised Restrictions on Use in Section 1. Revised the Updated the Hazards in Sections 2, 3, 4, 11, 12 and 15 to reflect the latest supplier information. Added H Codes and segregated Hazardous and Non-Hazardous components in Section 3. Revised the Appearance in Section 9 to match the production specification. Updated the Transport Information in Section 14.

SDS PREPARED BY Glen Pearson

SDS APPROVED BY Fred Allen