

**RESIFLOW® L-3075  
FLOW CONTROL AGENT  
FOR THE COATINGS INDUSTRY**

[www.estron.com](http://www.estron.com)



THE EDGE OF INNOVATION

### GENERAL DESCRIPTION

Resiflow® L-3075 is a specialty acrylic polymer additive provided at 75% solids in Solvent 100 (Hi-Sol 10) for use in coil coating systems. Resiflow® L-3075 affords excellent air release, improved film characteristics, and resistance to dirt-pick up. The recommended level of usage is between 0.2-2.0% based on coating resin weight. As with any additive, laboratory evaluation should be carried out for each formulation to determine the best processing method and optimum concentration.

### TYPICAL PROPERTIES\*

Appearance	Clear Liquid
Gardner Color	3 maximum
Specific Gravity (25/25)	0.98 – 1.02
Gardner Viscosity	S – W
Non-Volatile, weight %	73 – 77%
Acid value, mg KOH / gram	5 maximum

\* Not to be used for specification purposes

### REGULATORY LISTINGS

The components in this material are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories: EINECS (Europe), TSCA (USA)

### PACKAGING (NET WEIGHT)

44 lb. / 20.0 kg in steel pail

440 lb. / 199.6 kg in steel drum

### PRODUCT AVAILABILITY

This product is commercially available, but may require lead time.

### STORAGE AND HANDLING

Store closed containers in a dry, cool area and avoid excessive heat. Keep containers away from ignition sources or open flames. Shelf life of unopened containers is 1 year from date of shipment. See SDS for additional information.

### CONTACT INFORMATION

807 N. Main Street

P.O. Box 127

Calvert City, KY 42029 USA

(270) 395-4195 PHONE

(270) 395-5070 FAX

Revision Date: February 5, 2015

TDS Revised by: C. Miller

TDS Approved by: R. Auerbach