

**RESIFLOW® L-45D
FLOW CONTROL AGENT
FOR THE COATINGS INDUSTRY**

www.estron.com



THE EDGE OF INNOVATION

GENERAL DESCRIPTION

Resiflow® L-45D is an acrylic polymer solution used in high solids, UV curing, coil, and other coating systems. When incorporated at appropriate effective concentrations, it can eliminate air entrapment, correct surface imperfections such as pinholes, craters, and orange peel. Resiflow® L-45D can be used in acrylics, alkyds, phenolics, epoxies, polyesters, polyurethanes, nitrocellulose lacquers, and other systems.

As with other additive ingredients, laboratory evaluation is recommended to optimize the usage level and method of incorporation. Typical effective range is between 0.2-1.5% calculated on the coating binder.

TYPICAL PROPERTIES*

Appearance	Hazy Liquid
Viscosity	20 – 25 poise
Non-Volatile, weight %	78 – 82 %
Solvent	Butanol, Solvent 100

* Not to be used for specification purposes

REGULATORY LISTINGS

The components in this material are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories: AICS (Australia), DSL (Canada), ECL (Korea), EINECS (Europe), ENCS (Japan), IECSC (China), PICCS (Philippines), TSCA (USA)

PACKAGING (NET WEIGHT)

400 lb. / 181.4 kg in steel drum

PRODUCT AVAILABILITY

This product is made to order and requires lead time.

STORAGE AND HANDLING

Keep container tightly closed and store in a dry, well ventilated area away from extreme heat, open flame or sources of ignition. Store locked up. Shelf life of unopened containers is 1 year from date of shipment. See SDS for additional information.

CONTACT INFORMATION

807 N. Main Street

P.O. Box 127

Calvert City, KY 42029 USA

(270) 395-4195 PHONE

(270) 395-5070 FAX

Revision Date: October 9, 2017 TDS Revised by: A. Chizhikova TDS Approved by: F. Allen