

**RESIFLOW® LH-241
FLOW CONTROL AGENT
FOR THE COATINGS INDUSTRY**

www.estron.com



THE EDGE OF INNOVATION

GENERAL DESCRIPTION

Resiflow LH-241 is a specialty acrylic flow control additive that is in the reactive family of Resiflow products. Resiflow LH-241 is a viscous liquid additive that can be incorporated into a variety of binder chemistries to promote smoothness and gloss. Resiflow LH-241 is well suited for coil coatings and clearcoats. Typical dosage of Resiflow LH-241 is from 0.2 - 2%, but laboratory evaluation is highly recommended to determine the optimal concentration for a particular formula.

TYPICAL PROPERTIES*

Appearance	Clear Liquid
Gardner Color	2 maximum
Specific Gravity (25/25)	1.02 – 1.06
Gardner Viscosity, 80% SOLIDS IN XYLENE	W – Z
Non-Volatile, weight %	98.0% minimum

* Not to be used for specification purposes

REGULATORY LISTINGS

The components in this material are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories: EINECS (Europe)

PACKAGING (NET WEIGHT)

44 lb. / 20.0 kg in steel pail
440 lb. / 199.6 kg in steel drum

PRODUCT AVAILABILITY

This product is commercially available in standard packaging. Made to order packaging requires lead time.

STORAGE AND HANDLING

Keep container tightly closed and store in a dry, well ventilated area away from heat and sources of ignition. Store at less than 100°F (38°C). Shelf life of unopened containers is 1 year from date of shipment. See SDS for additional information.

CONTACT INFORMATION

807 N. Main Street
P.O. Box 127
Calvert City, KY 42029 USA

(270) 395-4195 PHONE
(270) 395-5070 FAX

Revision Date: June 10, 2014

TDS Revised by: G. Pearson

TDS Approved by: R. Auerbach