

**RESIFLOW® LH-241  
FLOW CONTROL AGENT  
FOR THE COATINGS INDUSTRY**

[www.estron.com](http://www.estron.com)



THE EDGE OF INNOVATION

### GENERAL DESCRIPTION

Resiflow LH-241 is a specialty acrylic flow control additive that is in the reactive family of Resiflow products. Resiflow LH-241 is a viscous liquid additive that can be incorporated into a variety of binder chemistries to promote smoothness and gloss. Resiflow LH-241 is well suited for coil coatings and clearcoats. Typical dosage of Resiflow LH-241 is from 0.2 - 2%, but laboratory evaluation is highly recommended to determine the optimal concentration for a particular formula.

### TYPICAL PROPERTIES\*

Appearance	Clear Liquid
Gardner Color	2 maximum
Specific Gravity (25/25)	1.02 – 1.06
Gardner Viscosity, 80% SOLIDS IN XYLENE	W – Z
Non-Volatile, weight %	98.0% minimum

\* Not to be used for specification purposes

### REGULATORY LISTINGS

The components in this material are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories: EINECS (Europe)

### PACKAGING (NET WEIGHT)

44 lb. / 20.0 kg in steel pail  
440 lb. / 199.6 kg in steel drum

### PRODUCT AVAILABILITY

This product is commercially available in standard packaging. Made to order packaging requires lead time.

### STORAGE AND HANDLING

Store in a dry, cool area and avoid excessive heat. Shelf life of unopened containers is one year from date of shipment. Refer to the SDS for additional information.

### CONTACT INFORMATION

807 N. Main Street  
P.O. Box 127  
Calvert City, KY 42029 USA

(270) 395-4195 PHONE  
(270) 395-5070 FAX

Revision Date: September 22, 2017

TDS Revised by: A. Chizhikova

TDS Approved by: F. Allen