

THE EDGE OF INNOVATION

GHS COMPLIANT SAFETY DATA SHEET

TO COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD $29\ CFR.1910.1200$ & THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS

SECTION 1: IDENTIFICATION

PRODUCT NAME Oxymelt A-4

MFR.'S CODE ID/SYNONYMS Oxymelt A-4

CAS NUMBER Proprietary

PRODUCT USE Phenoxy Resin

RESTRICTIONS ON USE For industrial use only

MANUFACTURER/SUPPLIER Estron Chemical, Inc.

ADDRESS 807 North Main Street, Calvert City, KY 42029 USA

GENERAL INFORMATION (270) 395-4195

EMERGENCY TELEPHONE CHEMTREC (800) 424-9300


SECTION 2: HAZARDS IDENTIFICATION

Signal Word: Danger

GHS Classification

Physical	Health	Environmental
OSHA Combustible Dust	Skin Corrosion/Irritation – Category 2	Hazardous to the Aquatic Environment,
	Serious Eye Damage/Eye Irritation -	Acute Hazard – Category 2
	Category 1	Hazardous to the Aquatic Environment,
	Skin Sensitization - Category 1	Chronic Hazard – Category 2
	Toxic to Reproduction - Category 2	
	Specific Target Organ Toxicity, Single	
	Exposure (Central Nervous System) –	
	Category 2	
	Specific Target Organ Toxicity, Single	
	Exposure (Respiratory Tract) – Category 3	
	Specific Target Organ Toxicity, Repeated	
	Exposure (Bladder, Kidneys, Liver) –	
	Category 2	

GHS Label



P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P308+311: IF exposed or concerned: Call a POISON CENTER or doctor/physician. P310: Immediately call a POISON CENTER or doctor/physician. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P321: Specific treatment (see supplemental first aid instructions on this label) P333+313: If skin irritation or a rash occurs: Get medical advice/attention. P362+P364: Take off immediately all contaminated clothing and wash it before reuse. P391: Collect spillage. Storage P403+233: Store in a well ventilated place. Keep container tightly closed. P405: Store locked up. Disposal P501: Dispose of contents/container to an authorized hazardous waste handler.

HAZARDS NOT OTHERWISE CLASSIFIED: None identified.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS	CAS#	%	CLASSIFICATION	H Codes
INGREDIENTS				
Phenoxy Resin	TSCA	85 - 90	OSHA Combustible Dust	None
	Listed		Skin Corrosion/Irritation – Category 2	H315
			Serious Eye Damage/Eye Irritation – Category 2A	H319
			Skin Sensitization - Category 1	H317
			Acute Aquatic Toxicity – Category 2	H401
			Chronic Aquatic Toxicity - Category 2	H411
Bisphenol A	80-05-7	10 - 15	Serious Eye Damage/Eye Irritation - Category 1	H318
			Skin Sensitization - Category 1	H317
			Toxic to Reproduction - Category 2	H361
			Specific Target Organ Toxicity, Single Exposure (Central	H371
			Nervous System) – Category 2	
			Specific Target Organ Toxicity, Single Exposure	H335
			(Respiratory Tract) – Category 3	
			Specific Target Organ Toxicity, Repeated Exposure	H373
			(Bladder, Kidneys, Liver) – Category 2	
			Acute Aquatic Toxicity – Category 2	H401
			Chronic Aquatic Toxicity - Category 2	H411

(See Section 8 for Exposure Limits)

SECTION 4: FIRST-AID MEASURES

SYMPTO	JMC.	OF EX	ZDOSI	IDE

ACUTE Serious eye damage. Skin, eye or respiratory tract irritation. Difficulty breathing. Nausea or

vomiting.

DELAYED Allergic skin reaction. Stinging, tearing, redness and swelling of the eyes. Rash, redness, itching

or burning of the skin. Shortness of breath.

INHALATION May cause respiratory irritation. Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

SKIN CONTACT Causes skin irritation. May cause an allergic skin reaction. Wash thoroughly with soap and water.

If skin irritation or a rash occurs: Get medical advice/attention.

EYE CONTACT Causes serious eye damage. Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing. Immediately call a POISON CENTER or

doctor/physician.

INGESTION If ingested, seek medical attention. Never give anything by mouth to an unconscious person.

Rinse mouth with water.

SPECIFIC TREATMENT No other specific treatments are known or have been identified.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABILITY CLASSIFICATION OSHA Combustible Dust

FLAMMABLE LIMITS LEL: No test data available

UEL: No test data available

HAZARDOUS COMBUSTION PRODUCTS Carbon monoxide and carbon dioxide.

EXTINGUISHING MEDIA Dry Chemical, Water Fog, and CO₂

UNUSUAL FIRE AND EXPLOSION HAZARDS Avoid generating dust; fine dust dispersed in air in sufficient concentrations

and in the presence of an ignition source is a potential dust explosion hazard.

SPECIAL FIRE FIGHTING PROCEDURES None known.

SPECIAL PROTECTIVE EQUIPMENT AND

As in any fire, wear self-contained positive-pressure breathing apparatus,

PRECAUTIONS FOR FIRE FIGHTERS (MSHA/NIOSH approved or equivalent) and full (Bunker) protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Prevent contact with skin, eyes and clothing. Ensure adequate ventilation.

PROTECTIVE EQUIPMENT See Personal Protective Equipment in Section 8.

EMERGENCY PROCEDURES Avoid unnecessary exposure to bystanders.

ENVIRONMENTAL PRECAUTIONS Obey relevant local, state, provincial and federal laws and regulations. Do not allow

the product to enter public drainage systems or open water courses.

METHODS AND MATERIALS FOR

CLEANING UP

Avoid creating excessive dust while collecting. Sweep or scoop into a suitable

container for disposal

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING Prevent contact with skin and eyes. Avoid inhalation. If necessary, use local

ventilation. Handle in accordance with good industrial hygiene and safety practice. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing and Handling of Combustible

Particulate Solids, for safe handling.

CONDITIONS FOR SAFE STORAGE Store locked up. Keep container tightly closed in a dry and well ventilated place.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

 INGREDIENTS
 CAS #
 %
 ACGIH TLV
 OSHA PEL

 Phenoxy Resin
 TSCA Listed
 85 - 90
 None established
 None established

Bisphenol A 80-05-7 $10-15 10 \text{mg/m}^3 15 \text{ mg/m}^3$

APPROPRIATE ENGINEERING CONTROLS

Showers, eyewash stations and ventilation systems. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area. Use only appropriately classified electrical equipment and powered industrial trucks.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE Safety glasses, goggles or face shield.

SKIN Impervious protective gloves and clothing as appropriate to prevent skin contact for the

exposure activity.

RESPIRATORY Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator

with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate

government standards such as NIOSH (US) or CEN (EU).

HYGIENE MEASURES Handle in accordance with good industrial hygiene and safety practices. When using, do not

eat, drink or smoke. Wash face, hands and any other exposed skin areas before breaks and at

the end of work. Wash contaminated clothing before re-use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Clear to Hazy Granules ODOR Mild, aromatic
ODOR THRESHOLD No test data available pH No test data available

MELTING POINT 90 - 100 °C BOILING POINT/RANGE >200 °C

FLASH POINT Over 200 °F EVAPORATION RATE No test data available

FLAMMABILITY OSHA Combustible Dust

FLAMMABLE LIMITS LOWER No test data available UPPER No test data available

VAPOR PRESSURE No test data available VAPOR DENSITY No test data available

RELATIVE DENSITY 1.2 @ 20 °C SOLUBILITY IN H₂O None

PARTITION COEFFICIENT

(n-octanol/water) No test data available TEMPERATURE No test data available

DECOMPOSITION

TEMPERATURE > 250 °C VISCOSITY Solid material

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY This product does not pose a significant reactivity hazard when stored

appropriately (see Section 7).

AUTOIGNITION

STABILITY Stable when maintained under recommended storage conditions.

CONDITIONS TO AVOID Dust accumulation in air or on surfaces, excessive heat, moisture and open

flame.

INCOMPATIBILE PRODUCTS Strong oxidizing agents, acids, Amines, Bases.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon dioxide and carbon monoxide.

POSSIBILITY OF HAZARDOUS REACTIONS Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

SYMPTOMS OF EXPOSURE

ACUTE Serious eye damage. Skin, eye or respiratory tract irritation. Difficulty breathing. Nausea

or vomiting.

DELAYED Allergic skin reaction. Stinging, tearing, redness and swelling of the eyes. Rash, redness,

itching or burning of the skin. Shortness of breath.

ACUTE TOXICITY

INHALATION May cause mechanical irritation if inhaled.

SKIN Causes skin irritation. May cause an allergic skin reaction.

EYES Causes serious eye damage.

INGESTION May be harmful if swallowed.

INHALATION TOXICITY LC50 Rat, 6 hours Bisphenol A 170 mg/m³

DERMAL TOXICITY LD₅₀ Rabbit Bisphenol A 3000 mg/kg

SKIN IRRITATION Draize, Rabbit, 24 hours Bisphenol A Mild

Primary Dermal

Irritiation Index No data available

EYE IRRITATION Draize, Rabbit, 24 hours Bisphenol A Severe

ORAL TOXICITY LD₅₀ Rat Bisphenol A 5000 mg/kg

SENSITIZATION Skin contact may cause an allergic skin reaction

CHRONIC EFFECTS

CARCINOGENICITY No component of this product present at levels greater than or equal

to 0.1% is identified as probable, possible or confirmed human

carcinogen by IARC, ACGIH, NTP or OSHA.

MUTAGENIC EFFECTS None known

REPRODUCTIVE TOXICITY Suspected human reproductive toxicant. Overexposure may cause

reproductive disorder(s) based on tests with laboratory animals.

TARGET ORGAN EFFECTS No test data available

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY Toxic to aquatic life with long lasting effects.

TOXICITY TO FISH LC₅₀ Pimephales promelas, 96 hours Polymer 1.75 mg/l

Bisphenol A 4.6 mg/l

TOXICITY TO DAPHNIA EC₅₀ Daphnia magna, 48 hours Polymer 1.7 mg/l

Bisphenol A 1.8 mg/L

TOXICITY TO ALGAE IC₅₀ Pseudokirchneriella subcapitata, 96 hours Bisphenol A 2.73 mg/l

PERSISTANCE AND

DEGRADABILITY No data available

BIOACCUMULATIVE

POTENTIAL Indication of bioaccumulation with a low potential.

MOBILITY IN SOIL No data available

OTHER ADVERSE There is a potential for environmental hazard in the event of unprofessional handling

EFFECTS or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Hazardous waste, dispose of in accordance with local, state and federal

regulations. Contact a licensed professional waste disposal service to dispose

of this material.

US EPA WASTE NUMBER & DESCRIPTION No information available

SECTION 14: TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

U.S. DOT

Not dangerous goods

Estron may choose to ship this product domestically as a hazardous material using one of the other codes shown in this section.

ICAO / IATA

Proper Shipping Name: Environmentally hazardous substance,

solid, n.o.s.

Technical Shipping Name (If n.o.s.): Bisphenol A epoxy resin

Hazard Class: 9 ID Number: UN 3077 Packing Group: PG III Label: Miscellaneous

Marine Pollutant: Marine Pollutant

IMDG

Proper Shipping Name: Environmentally hazardous substance,

solid, n.o.s.

Technical Shipping Name (If n.o.s.): Bisphenol A epoxy resin

Hazard Class: 9 ID Number: UN 3077 Packing Group: PG III Label: Miscellaneous

Marine Pollutant: Marine Pollutant

ADR/RID

Proper Shipping Name: Environmentally hazardous substance,

solid, n.o.s.

Technical Shipping Name (If n.o.s.): Bisphenol A epoxy resin

Classification: 9 UN#: 3077 Packing Group: III

TDG

Proper Shipping Name: Environmentally hazardous substance,

solid, n.o.s.

Technical Shipping Name (If n.o.s.): Bisphenol A epoxy resin

Hazard Class: 9 ID Number: UN 3077 Packing Group: PG III Label: Miscellaneous

Marine Pollutant: Marine Pollutant

SECTION 15: REGULATORY INFORMATION

The components in this product are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories as indicated by an "X":

AICS	Australian Inventory of Chemical Substances	X
DSL	Canadian Domestic Substances List	X
ECL	Korean Existing Chemicals List	
ELINCS	European List of Notified Chemical Substances	
ENCS	Japanese Existing and New Chemical Substances	X
IECSC	Inventory of Existing Chemical Substances in China	X
ISRAEL	Proposed Israel Hazardous Substances List	
NDSL	Canadian Non-Domestic Substances List	
NZIoC	New Zealand Inventory of Chemicals	X
PICCS	Philippines Inventory of Chemicals and Chemical Substances	X
SWISS	Giftliste 1 and Inventory of Notified New Substances	X
TCSI	Taiwan Chemical Substances List	X
TSCA	US Toxic Substances Control Act	X

INTERNATIONAL REGULATIONS

EU REGULATION (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization,

Substances of Very High Concern: This product contains Bisphenol A, an ECHA SVHC

listed substance.

REACH All components of this product are REACH registered per ECHA requirements.

C.D. 96/82/EC Council Directive 96/82/EC, Annex I not mentioned by name. With regard to possibly appropriate

decomposition products see Chapter 10.

WHMIS (Canada) Class D-2B: Material causing other toxic effects (Toxic).

FEDERAL REGULATIONS

SARA 313

This product does not contain any chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355)

SARA Section 311/312 (40 CFR 370) Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Pressure Hazard	No
Reactivity Hazard	No

CERCLA

This product, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional or state level pertaining to releases of this product.

CLEAN AIR ACT

This product does not contain any substances regulated as hazardous air pollutants (HAPS under Section 112 of the Clean Air Act Amendments of 1990.

U.S. STATE REGULATIONS

RIGHT TO KNOW

The Listing requirements of the Right to Know (RTK) legislation varies by state. All information for NJ, PA, MA and other states can be derived from the listing of hazardous and non-hazardous components in Sections 2 and 15 of this Safety Data Sheet.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

WARNING! This product contains a chemical (Bisphenol A) known to the State of California to cause birth defects or other reproductive harm.

SECTION 16: OTHER INFORMATION

DISCLAIMER

This product is intended for industrial use only and should be used in accordance with the manufacturer's recommendations. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. This SDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

DATE OF REVISION September 4, 2019, replaces the August 6, 2018 version.

REASON FOR REVISION Removed ECL listing in Section 15.

SDS PREPARED BY Glen Pearson

SDS APPROVED BY Robert Auerbach