

**GHS COMPLIANT SAFETY DATA SHEET**

TO COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR.1910.1200 & THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS

**SECTION 1: IDENTIFICATION**

PRODUCT NAME	Isocryl® H-112BA
MFR.'S CODE ID/SYNONYMS	Isocryl® H-112BA, DS13-47
CAS NUMBER	Mixture (see Sections 3 or 8)
PRODUCT USE	Resin for coatings
RESTRICTIONS ON USE	For industrial use only
MANUFACTURER/SUPPLIER	Estron Chemical, Inc.
ADDRESS	807 North Main Street, Calvert City, KY 42029 USA
GENERAL INFORMATION	(270) 395-4195
EMERGENCY TELEPHONE	CHEMTREC (800) 424-9300



**SECTION 2: HAZARDS IDENTIFICATION**

**Signal Word:** *Warning*

**GHS Classification**

Physical	Health	Environmental
Flammable Liquids – Category 3	Acute Toxicity (Oral, Inhalation) – Category 4 Skin Corrosion/Irritation – Category 2 Eye Damage/Irritation – Category 2A Specific Target Organ Toxicity, Single Exposure (Central Nervous System) – Category 3	Hazardous to the Aquatic Environment, Acute Hazard – Category 3 Hazardous to the Aquatic Environment, Chronic Hazard – Category 3

**GHS Label**

	
<p><b>Symbols:</b> Flame      Exclamation Mark</p>	
<p><b>Hazard Statements</b></p> <p>H226: Flammable liquid and vapour H302: Harmful if swallowed H315: Causes skin irritation H319: Causes serious eye irritation H332: Harmful if inhaled H335: May cause respiratory irritation H336: May cause drowsiness or dizziness H412: Harmful to aquatic life with long lasting effects</p>	<p><b>Precautionary Statements</b></p> <p><i>Prevention</i></p> <p>P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking. P233: Keep container tightly closed. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/light/equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P264: Wash exposed skin thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment P280: Wear protective gloves/protective clothing/eye protection/face protection.</p> <p><i>Response</i></p> <p>P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P302+352: IF ON SKIN: Wash with plenty of soap and water.</p>

	<p>P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+340+312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.</p> <p>P321: Specific treatment (see supplemental first aid instructions on this label)</p> <p>P330: Rinse mouth.</p> <p>P332+313: If skin irritation occurs: Get medical advice/attention.</p> <p>P337+313: If eye irritation persists get medical advice/attention.</p> <p>P362+P364: Take off contaminated clothing and wash it before reuse.</p> <p>P370+378: In case of fire: Use foam, dry chemical powder, carbon dioxide or water fog to extinguish.</p> <p><i>Storage</i></p> <p>P403+233+235: Store in a well ventilated place. Keep container tightly closed. Keep cool.</p> <p>P405: Store locked up.</p> <p><i>Disposal</i></p> <p>P501: Dispose of contents/container to an authorized hazardous waste handler.</p>
--	--

HAZARDS NOT OTHERWISE CLASSIFIED: None identified.

**SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENTS	CAS #	%	CLASSIFICATION	H CODES
Methyl Amyl Ketone	110-43-0	18 - 22	Flammable Liquids – Category 3 Acute Toxicity (Oral, Inhalation) – Category 4 Skin Corrosion/Irritation – Category 2 Eye Damage/Irritation – Category 2B Specific Target Organ Toxicity, Single Exposure (Central Nervous System) – Category 3 Hazardous to the Aquatic Environment, Acute Hazard – Category 3 Hazardous to the Aquatic Environment, Chronic Hazard – Category 3	H226 H302, H332 H315 H320 H335, H336 H402 H412
n-Butyl Acetate	123-86-4	8 - 12	Flammable Liquids – Category 3 Skin Corrosion/Irritation – Category 2 Eye Damage/Irritation – Category 2A Specific Target Organ Toxicity, Single Exposure (Central Nervous System) – Category 3 Hazardous to the Aquatic Environment, Acute Hazard – Category 3	H226 H315 H319 H336 H412

(See Section 8 for Exposure Limits)

NON-HAZARDOUS INGREDIENTS	CAS #	%
Acrylic Polymers	Proprietary	68 - 72

**SECTION 4: FIRST-AID MEASURES**

**SYMPTOMS OF EXPOSURE**

ACUTE	Drowsiness or dizziness. Skin and/or eye irritation. Respiratory irritation. Nausea.
DELAYED	Stinging, tearing, redness and swelling of the eyes. Redness or burning of the skin. Headache. Nausea. Unconsciousness.

INHALATION	Harmful if inhaled. May cause drowsiness or dizziness. May be irritating to the respiratory tract. If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing is labored or with coughing, give 100% supplemental oxygen. If not breathing begin artificial respiration and get medical aid.
------------	--

SKIN CONTACT	Causes skin irritation. If on skin (or hair), remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Wash thoroughly with soap and water. If skin irritation occurs, consult a doctor.
EYE CONTACT	Causes eye irritation. Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Wash with plenty of water for 15 minutes. Consult a physician.
INGESTION	Harmful if swallowed. Do NOT induce vomiting unless directed by medical personnel. If ingested, call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.
SPECIFIC TREATMENT	No other specific treatments are known or have been identified.

## **SECTION 5: FIRE FIGHTING MEASURES**

FLAMMABILITY CLASSIFICATION	Flammable Liquid Class IC
FLAMMABLE LIMITS	LEL: 1.1 %, by volume of solvent. UEL: 7.9 %, by volume of solvent.
HAZARDOUS COMBUSTION PRODUCTS	Carbon Dioxide, Carbon Monoxide.
EXTINGUISHING MEDIA	Dry Chemical, Foam, CO <sub>2</sub> , Water Fog
UNUSUAL FIRE AND EXPLOSION HAZARDS	Solvent vapors may travel in the work place. Since even residual amounts can ignite explosively, ensure all ignition sources are removed from the area. Solid stream of water may spread fire.
SPECIAL FIRE FIGHTING PROCEDURES	Wear self-contained breathing apparatus and protective suit when fighting fire. Solid streams of water may spread the fire.
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS	As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full (Bunker) protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
PROTECTIVE EQUIPMENT	See Personal Protective Equipment in Section 8.
EMERGENCY PROCEDURES	Avoid unnecessary exposure to bystanders, prevent contact with open flames or high heat sources. Isolate the area and eliminate all ignition sources. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment.
ENVIRONMENTAL PRECAUTIONS	Obey relevant local, state, provincial and federal laws and regulations. Do not allow the product to enter public drainage systems or open water courses.
METHODS AND MATERIALS FOR CLEANING UP	Absorb the product onto vermiculite, floor absorbent or other absorbent materials, such as dry-lime, sand, or soda ash. Sweep or scoop into a suitable container for disposal. Ventilate area and wash spill site after material pickup is complete.

## **SECTION 7: HANDLING AND STORAGE**

PRECAUTIONS FOR SAFE HANDLING	Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors. Use with adequate ventilation. Ground and bond all containers and handling equipment. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges. Emptied containers may still be hazardous. Do not cut, drill, grind, weld or perform similar actions on or near empty containers. Wear appropriate protective equipment when handling this material (See Section 8).
CONDITIONS FOR SAFE STORAGE	Store in cool, dry, well-ventilated areas. Keep containers closed. Do not store near extreme heat, open flame or sources of ignition. The product shelf life is two years from date of manufacture in an unopened container stored at 20 °C.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

INGREDIENTS	CAS #	%	ACGIH TLV	OSHA PEL
Acrylic Polymers	Proprietary	68 - 72	<i>None established</i>	<i>None established</i>
Methyl Amyl Ketone	110-43-0	18 - 22	50 ppm	100 ppm
n-Butyl Acetate	123-86-4	8 - 12	150 ppm	150 ppm

APPROPRIATE ENGINEERING CONTROLS Showers, eyewash stations and explosion-proof ventilation systems.

### PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE	Chemical splash goggles or face shield.
SKIN	Wear resistant gloves (consult your safety equipment supplier) and impervious protective clothing as appropriate to prevent skin contact.
RESPIRATORY	An appropriate NIOSH approved respirator where exposure limits are exceeded.
HYGIENE MEASURES	Handle in accordance with good industrial hygiene and safety practices. When using, do not eat, drink or smoke. Wash face and hands before breaks and at the end of work. Wash contaminated clothing before re-use.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Clear liquid	ODOR	Strong, esteric
ODOR THRESHOLD	No test data available	pH	No test data available
MELTING POINT	No test data available	BOILING POINT/RANGE	124 °C @ 760 mmHg
FLASH POINT	27 °C	EVAPORATION RATE	0.34 (n-Butyl Acetate)
FLAMMABILITY	Flammable Liquid Class IC		
FLAMMABLE LIMITS	LOWER 1.1 %, <i>by volume of solvent</i>	UPPER 7.9 %, <i>by volume of solvent</i>	
VAPOR PRESSURE	8.4 mmHg @ 20 °C	VAPOR DENSITY	3.94 (Air = 1)
RELATIVE DENSITY	1.0 – 1.05 @ 20 °C	SOLUBILITY IN H <sub>2</sub> O	<i>Solvent – No data</i> <i>Polymers - Nil</i>
PARTITION COEFFICIENT (n-octanol/water)	No test data available	AUTOIGNITION TEMPERATURE	393 °C
DECOMPOSITION TEMPERATURE	> 250 °C (Polymer)	VISCOSITY	No test data available
% VOLATILE	28 - 32%	SOFTENING POINT	No test data available

## **SECTION 10: STABILITY AND REACTIVITY**

REACTIVITY	This product does not pose a significant reactivity hazard when stored appropriately (see Section 7).
STABILITY	This product is stable when stored appropriately.
CONDITIONS TO AVOID	All ignition sources, heat and open flames.
INCOMPATIBLE PRODUCTS	Strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon Dioxide, Carbon Monoxide.
POSSIBILITY OF HAZARDOUS REACTIONS	Will not occur

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### SYMPTOMS OF EXPOSURE

ACUTE	Drowsiness or dizziness. Skin and/or eye irritation. Respiratory irritation. Nausea.
DELAYED	Stinging, tearing, redness and swelling of the eyes. Redness or burning of the skin. Headache. Nausea. Unconsciousness.

### ACUTE TOXICITY

INHALATION	Harmful if inhaled. May cause drowsiness or dizziness. May be irritating to the respiratory tract.
------------	--

SKIN	Causes skin irritation.			
EYES	Causes eye irritation.			
INGESTION	Harmful if swallowed.			
INHALATION TOXICITY	LC <sub>50</sub> Rat, 4 hours	MAK Butyl Acetate Polymers	> 16.7 mg/l 390 mg/l, 4 h. Not established	
DERMAL TOXICITY	LD <sub>50</sub> Rabbit	MAK Butyl Acetate Polymers	> 2000 mg/kg >17600 mg/kg Not established	
SKIN IRRITATION	Draize, Rabbit, 4 hours	MAK Butyl Acetate Polymers	Skin irritant 500 mg/m <sup>3</sup> No data available	Moderate
EYE IRRITATION	Draize, Rabbit Human	MAK Butyl Acetate	Eye irritant 300 ppm	Moderate
	Draize, Rabbit, 24 hours	Butyl Acetate Polymers	100 mg No data available	Moderate
ORAL TOXICITY	LD <sub>50</sub> Rat	MAK Butyl Acetate Polymers	1670 mg/kg >10000 mg/kg Not established	
SENSITIZATION	Lymph node assay, mouse		Did not cause sensitization	
<b>CHRONIC EFFECTS</b>				
CARCINOGENICITY		Not listed as a carcinogen by ACGIH, IARC, or NTP		
MUTAGENIC EFFECTS		None known		
REPRODUCTIVE TOXICITY		None known		
TARGET ORGAN EFFECTS		Narcotic Effects (Inhalation)		

## **SECTION 12: ECOLOGICAL INFORMATION**

ECOTOXICITY	Harmful to aquatic life with long lasting effects.		
TOXICITY TO FISH	LC <sub>50</sub> Pimephales promelas, 96 h	MAK Butyl Acetate Polymers	131 mg/l 18 mg/l Not established
TOXICITY TO DAPHNIA	EC <sub>50</sub> Daphnia magna, 48 h	MAK Butyl Acetate Polymers	> 100 mg/l 44 mg/l Not established
TOXICITY TO ALGAE	EC <sub>50</sub> Selenastrum capr., 72 h EC <sub>50</sub> Desmodesmus subsp., 72 h	MAK Butyl Acetate Polymers	98.2 mg/l 675 mg/l Not established
PERSISTANCE AND DEGRADABILITY	No data available for polymers. MAK: Activated sludge, 28 days, 69% biodegradation. <i>Readily biodegradable, according to appropriate OECD test</i>		
BIOACCUMULATIVE POTENTIAL	No data available		
MOBILITY IN SOIL	No data available		
OTHER ADVERSE EFFECTS	None known		

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### **WASTE DISPOSAL**

Dispose of in accordance with local, state and federal regulations. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Empty containers may retain some product residues. Vapor from product residues may create a flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been thoroughly cleaned. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3.

US EPA WASTE NUMBER & DESCRIPTION No information available

### **SECTION 14: TRANSPORT INFORMATION**

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

#### **U.S. DOT**

Proper Shipping Name: Resin Solution, *flammable*  
Classification: 3  
UN#: 1866  
Packing Group: III  
Hazard Label: Flammable Liquid

#### **ICAO / IATA**

Proper Shipping Name: Resin Solution, *flammable*  
Classification: 3  
UN#: 1866  
Packing Group: III  
Hazard Label: Flammable Liquid

#### **IMDG**

Proper Shipping Name: Resin Solution, *flammable*  
Classification: 3  
UN#: 1866  
Packing Group: III  
EmS#: F-E, S-E  
Hazard Label: Flammable Liquid

#### **ADR/RID**

Proper Shipping Name: Resin Solution, *flammable*  
Classification: 3  
UN#: 1866  
Packing Group: III  
Hazard Label: Flammable Liquid

### **SECTION 15: REGULATORY INFORMATION**

The components in this product are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories as indicated by an "X":

AICC	Australian Inventory of Industrial Chemicals	X
DSL	Canadian Domestic Substances List	X
ECL	Korean Existing Chemicals List	
ENCS	Japanese Existing and New Chemical Substances	X
IECSC	Inventory of Existing Chemical Substances in China	X
INSQ	National Inventory of Chemical Substances in Mexico	
NDSL	Canadian Non-Domestic Substances List	
NZIoC	New Zealand Inventory of Chemicals	X
PICCS	Philippines Inventory of Chemicals and Chemical Substances	X
TCSI	Taiwan Chemical Substances List	X
TSCA	US Toxic Substances Control Act	X
VNECI	Vietnam National Existing Chemical Inventory	X

#### **INTERNATIONAL REGULATIONS**

##### **EU REGULATION**

(EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization, *Substances of Very High Concern*: This product does not contain any SVHC listed substances.

##### **REACH**

One or more components of this product are not REACH registered. Import quantities may be subject to limitation.

##### **C.D. 96/82/EC**

Council Directive 96/82/EC, Annex I not mentioned by name. With regard to possibly appropriate decomposition products see Chapter 10.

## FEDERAL REGULATIONS

SARA 313 This product does not contain any chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

### SARA Section 311/312 (40 CFR 370) Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Pressure Hazard	No
Reactivity Hazard	No

CERCLA This product, as supplied, contains substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional or state level pertaining to releases of this product.

**n-Butyl Acetate** (123-86-4): 5000 lb final RQ; 2270 kg final RQ.

CLEAN WATER ACT This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CLEAN AIR ACT This product does not contain any substances regulated as hazardous air pollutants (HAPS under Section 112 of the Clean Air Act Amendments of 1990).

OTHER FEDERAL None known

## U.S. STATE REGULATIONS

RIGHT TO KNOW The Listing requirements of the Right to Know (RTK) legislation varies by state. All information for NJ, PA, MA and other states can be derived from the listing of hazardous and non-hazardous components in Sections 2 and 15 of this Safety Data Sheet.

CALIFORNIA PROP 65 No substances known to the state of California to cause cancer and/or reproductive toxicity were intentionally included in this product. However, the product may contain unknown trace amounts of substances known to the state of California to cause cancer and/or reproductive toxicity: (*styrene*).

## SECTION 16: OTHER INFORMATION

DISCLAIMER This product is intended for industrial use only and should be used in accordance with the manufacturer's recommendations. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. This SDS has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

DATE OF REVISION June 21, 2023, *replaces the February 22, 2023 version*

REASON FOR REVISION Updated the relative density in Section 9 pursuant to PCF 23-014.

SDS PREPARED BY Glen Pearson

SDS APPROVED BY Robert Auerbach